

M=BUS LAB Fire and Measurement Board (FAM)

Ignites pyrotechnical devices such as airbags or seat belt pretensioners and records ignition current and voltage.

- | Support of 4 or 8 fire channels
- | Individually programmable timers
- | Operation independent from other M=BUS devices possible
- | Squib recognition
- | Resistance measuring
- | Mechanical and electrical interlock



TECHNICAL SPECIFICATIONS


Supported channels	4 or 8
Supply voltage	18...22 VDC
Power consumption (unloaded)	13 W
Trigger	Trigger-bus (RS 485), 5V-TTL compatible; insulated 300 V
Conformity	SAE J211 / ISO 6487
Resolution	16 bit
Sampling rate	400 kHz
Max. recording time	300 ms Pre-trigger and delay: 60 ms Post-trigger and delay: 240 ms
DC-Ignition	12 V, adjustable current: 0.1...8 A in steps of 0.1 A @ 1 Ω
Ignition energy	280 mJ
Ignition delay (set per software)	Min. 0.01 ms in steps of 0.01 ms
Ignition pulse duration (set per software)	Min. 0.1 ms in steps of 0.01 ms
Communication	IEEE 802.3 i/u Ethernet 10 Mbit/s / 100 Mbit/s
Dimensions	4 slots

Weight	4 channel: 400 g 8 channel: 500 g
Operating temperature	0...50 °C
Humidity range	10...70 % RH

- Scope of supply**
- | M=BUS LAB Fire and Measurement Board
 - | Connecting cable for M=BUS Pro / Lab Ethernet Gateway (0.3 m)
 - | Connecting cable for power, network and trigger (0.3 m)


- Required equipment**
- | M=BUS LAB housing
 - | CrashSoft control software

PIN ASSIGNMENT



Pin	Description	Pin	Description
1	+ for anode of the LED in the release connector	3	Release input via bridge in the release connector (fire only)
2	- for cathode of the LED in the release connector	4	Release input via bridge in the release connector (fire only)

Figure 1: Pin assignment release connector for fire or safe (socket view, device)
Use this plug: LEMO FGG.0B.304...



Pin	Description	Pin	Description
1	Fire in / out -	4	Fire sense + -: Sense line to the + connection of the ignition tablet (to measure the ignition voltage)
2	Fire sense -: Sense line to the - connection of the ignition tablet (to measure the ignition voltage)	5	Fire in +
3	Fire out +: + connection of the ignition tablet		

Figure 2: Pin assignment ignition channel (socket view, device)
Use this plug: LEMO FGG.1B.305

Current ramp-up time as a function of load resistance (Ohm) and selected current range (Ampere)

	With R = 1 Ω						With R = 10 Ω
Set current	1 A	2 A	3 A	4 A	5 A	6 A	1 A
\emptyset current ramp-up time per 1A	182 μ s	68 μ s	42 μ s	31 μ s	26 μ s	21 μ s	760 μ s






Figure 3: M=BUS Ethernet Gateway adapter cable



Pin	Description	Pin	Description
1	Network TX +	9	485 A
2	Network TX -	10	485 B
3	Network RX +	11	Supply +22 V
4	Network RX -	12	Supply +22 V
5	Trigger 5 V / 120 mA	13	Supply +22 V
6	Trigger signal B	14	Ground
7	Trigger signal A	15	Ground
8	Trigger isolated ground	16	Ground

Figure 4: M=BUS system connection (socket view, device)


Use this plug: LEMO FGC.2B.316...



Pin	Description	Pin	Description
1	Supply +22 V	3	485 A
2	Ground	4	485 B

Figure 5: Pin assignment power (socket view, cable)


Use this plug: LEMO FGG.2B.304...



Pin	Description	Pin	Description
1	Trigger 5 V / 120 mA	3	Trigger signal A
2	Trigger signal B	4	Trigger isolated ground

Figure 6: Pin assignment trigger bus (socket view, cable)

Use this plug: LEMO FGG.1B.304...



Pin	Description	Pin	Description
1	Network TX +	4	Network RX -
2	Network TX -	5	Not connected
3	Network RX +		

Figure 7: Pin assignment network (socket view, cable)

Use this plug: LEMO FGG.1B.305...

TRIGGER BUS




Figure 8: Schematic for trigger switch




Figure 9: Schematic for optocoupler




Figure 10: Schematic for TTL